	CITY OF CURB CUT AND D		
Αľ	PPLICANT NAME:DDRESS:		PHONE:
W	ORK LOCATION:		
Th	e street, alley, or public place that the new drivewa	av will tie	into is: (Check one)
	Gravel with ditches	1 1	Strip paved with ditches
	Gravel without ditches		Strip paved without ditches
	Curb & Gutter w/Barrier Curb		Curb & Gutter w/Rolled Curb
	pplicant agrees to the following City of Ken	100 Marie 1	
*	The flow line of the gutter has to be maintained. Driveways that tie into a street with barrie curbs have to be replaced with a driveway cut that maintains the gutter flow line. The back of the barrier curb cannot simply be knocked off.		
*	Streets with ditches must have the flow in the ditch maintained. A minimum 15-inch diameter culvert must be installed under the driveway and extend a minimum of two fee beyond the gravel on each side of the driveway at the base of the culvert.		
*	All frost-susceptible material should be removed from the portion of the driveway that is within the public right-of-way. If the road is paved, the driveway approach that is within the right-of-way must be paved.		
*	The public right-of-way must be restored to the grade and condition originally found and gravel, paving, seal coating, ditches, culverts, and curbs restored to original condition.		
*	Special Conditions:		
			DATE:
Sig	nature of Applicant		
	APPROV	VED BY	/: <u> </u>
CA	LL 283-8236 for an inspection once the	work	is complete.

Building Permit No.: _____

PERMIT TO BE AVAILABLE AT PROJECT SITE

INSPECTED BY: ______